




Conexões tubulares em Aço Inox conforme ANSI B16.9




CURVA 90°




CURVA 45°




TEE




REDUÇÃO EXCÊNTRICA




REDUÇÃO CONCÊNTRICA




PESTANA CURTA ESTAMPADA



PESTANA CURTA STUB END
MSS SP-43



PESTANA STUB END LONGA



CAPS

Diâmetro		SCH				C	F	G	H	J	L	M	N	R	P	Tipo	
Bitola	mm	5s	10s	40s	80s											A	B
½	21,3	1,65	2,11	2,77	3,73	25	38	25	-	44	35	76	51	2	16	3,2	0,8
¾	26,7	1,65	2,11	2,87	3,91	29	38	25	38	54	43	76	51	2	19	3,2	0,8
1	33,4	1,65	2,77	3,38	4,55	38	38	38	51	62	51	102	51	2	22	3,2	0,8
1.1/4	42,2	1,65	2,77	3,56	4,85	48	48	38	51	72	64	102	51	2	25	4,8	0,8
1.1/2	48,4	1,65	2,77	3,68	5,08	57	57	38	64	80	73	102	51	2	29	6,3	0,8
2	60,3	1,65	2,77	3,91	5,54	64	76	38	76	100	92	152	64	2	35	8,0	0,8
2.1/2	73,1	2,11	3,05	5,16	7,01	76	95	38	89	118	105	152	64	2	44	8,0	0,8
3	88,9	2,11	3,05	5,49	7,62	86	114	51	89	130	127	152	64	2	51	9,5	0,8
4	114,3	2,11	3,05	6,02	8,56	105	152	64	102	165	157	152	76	2	64	11,1	0,8
6	168,3	2,77	3,4	7,11	10,97	143	229	89	140	216	216	203	89	2	95	12,7	1,6
8	219,1	2,77	3,76	8,18	12,70	178	305	102	152	274	270	203	102	2	127	12,7	1,6
10	273,0	3,40	4,19	9,27	12,70	216	381	127	178	333	324	254	127	2	159	12,7	1,6
12	323,8	3,96	4,57	9,27	12,70	254	457	152	203	390	381	254	152	2	190	12,7	1,6
14	355,6	3,96	4,78	-	-	279	533	165	330	420	413	305	152	2	222	12,7	1,6
16	406,4	4,20	4,78	-	-	305	610	178	356	470	470	305	152	2	254	12,7	1,6
18	457,8	4,20	4,78	-	-	343	686	203	381	520	533	305	152	2	286	12,7	1,6
20	508,0	4,78	5,54	-	-	381	762	228	508	570	584	305	152	2	318	12,7	1,6
22	558,8	5,54	6,35	-	-	419	838	254	508	-	641	305	152	2	343	12,7	1,6
24	609,6	-	6,35	-	-	432	914	267	508	675	692	305	152	2	381	12,7	-

* Tabela para simples consulta, a norma ANSI B16.9 apresenta mais informações que devem ser consideradas.